

BORELINE

the flexible rising main

Brought to you by



GRN Coupling System for 1" to 4" risers

The GRN coupling system provides a means to obtain the benefits of **BORELINE** flexible rising main at a cost effective price. Using the latest engineering plastics and advanced manufacturing processes, **BORELINE** Glass Reinforced Nylon couplings give the same performance as stainless steel at a fraction of the cost.

BORELINE is supplied cut to length to suit your borehole and includes cable straps to support the power cable. **BORELINE** is specifically designed to take the full weight of itself, pump, motor, cable & water so requires no support ropes or wires.

BORELINE BENEFITS

- Quick, easy, inexpensive installation and retrieval
- Fully resistant to corrosion, scaling & biological growth
- Light weight
- Excellent hydraulic performance
- WRAS Approved
- 5 Year Warranty



Nominal Size	1"	1½"	2"	2½"	3"	4"
Inside Diameter	25mm	40mm	50mm	65mm	76mm	102mm
Maximum set depth	100m	100m	100m	100m	75m	75m
Operating Pressure	20 bar	20 bar	20 bar	20 bar	15 bar	15 bar
Maximum Working Load	0.40 tonne	0.8 tonne	1 tonne	1.5 tonne	1.5 tonne	2 tonne
Minimum Well Diameter	76mm	102mm	125mm	152mm	152mm	203mm
Coupling Torque Settings	10Nm	10Nm	12Nm	20Nm	30Nm	30Nm
Weight Per Metre	0.24 kg	0.38 kg	0.55 kg	0.85 kg	0.95 kg	1.4 kg
Coupling Weight	0.2 kg	0.3 kg	0.7 kg	1.3 kg	1.5 kg	2.3 kg

Specification

Water pH **4 - 9** Average Extension **3%**
 Maximum Swell **15%** Max Operating Temp **40°C**



**CONTACT
US TODAY**

Proquip Direct Limited, Unit 34 Silverwing Ind Est. Imperial Way, Croydon, Surrey, CR0 4RR
 Tel: 020 8712 5982 Fax: 020 8712 5983 sales@proquipdirect.com www.proquipdirect.com